Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025



Version 4.0. Supersedes version: 3.0

Page 1 / 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Gear oil 75W - 80 Article number: 180073

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictogramsnoneSignal wordnoneHazard statementsnone

Special labelling EUH210 Safety data sheet available on request.

Contains: 3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid. EUH208 May

produce an allergic reaction.

2.3 Other hazards

Environmental hazardsDoes not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards No particular hazards known.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025

Version 4.0. Supersedes version: 3.0

Page 2 / 12

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
1 - < 10	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)
	CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX
	GHS/CLP: Asp. Tox. 1: H304
0,1 - <0,93	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	EINECS/ELINCS: 931-384-6, Reg-No.: 01-2119493620-38-XXXX
	GHS/CLP: Acute Tox. 4: H302 - Eye Irrit. 2: H319 - Skin Sens. 1: H317 - Aquatic Chronic 2: H411
	SCL [%]: 9,39 - 100: Skin Sens. 1: H317, >50 - 100: Eye Irrit. 2: H319
0,1 - 1	3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid
	CAS: 268567-32-4, EINECS/ELINCS: 434-070-2, Reg-No.: 01-2119658068-31-XXXX
	GHS/CLP: Eye Dam. 1: H318 - Skin Sens. 1B: H317 - Aquatic Chronic 3: H412

Comment on component parts For full text of H-statements: see SECTION 16.

Contains less than 3% w/w DMSO-extract (only for mineral oils)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Do not induce vomiting.

Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Headache

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025



Version 4.0. Supersedes version: 3.0 Page 3 / 12

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

Use only in well-ventilated areas. Use solvent-resistant equipment.

The product is combustible.

Do not eat, drink or smoke when using this product.

After worktime and before work breaks the affected skin areas must be thoroughly cleaned.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container in a well-ventilated place.

Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025



Version 4.0. Supersedes version: 3.0 Page 4 / 12

SECTION 8: Exposure controls / personal protection

Substance

Substance

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

not relevant

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Gabotano		
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4		
Industrial, dermal, Long-term - systemic effects, 1.25 mg/kg bw/d (AF=100)		
Industrial, inhalative, Long-term - systemic effects, 4,4 mg/m³ (AF=25)		
general population, inhalative, Long-term - systemic effects, 1.1 mg/m³ (AF=50)		
general population, dermal, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)		
general population, oral, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m³		
Industrial, inhalative, Long-term - local effects, 5,58 mg/m³		
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
general population, oral, Long-term - local effects, 740 μg/kg bw/day		
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		
Industrial, inhalative, Long-term - systemic effects, 4.28 mg/m³		
Industrial, dermal, Long-term - systemic effects, 12.5 mg/kg bw/day		
Industrial, dermal, Long-term - local effects, 160 μg/cm²		
Industrial, dermal, Acute - local effects, 160 μg/cm²		
general population, inhalative, Long-term - systemic effects, 1.09 mg/m³		
general population, dermal, Long-term - systemic effects, 6.25 mg/kg bw/day		
general population, dermal, Long-term - local effects, 160 μg/cm²		
general population, dermal, Acute - local effects, 160 μg/cm ²		
general population, oral, Long-term - systemic effects, 250 μg/kg bw/day		

PNEC

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4		
freshwater, 36 μg/L		
seawater, 3,6 µg/L		
sewage treatment plants (STP), 10 mg/L		
sediment (freshwater), 1,42 mg/kg sediment dw		
sediment (seawater), 142 µg/kg sediment dw		
soil, 496 μg/kg soil dw		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
oral (food), 9,33 mg/kg food		
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		
freshwater, 2.4 µg/L		
seawater, 240 ng/L		
sewage treatment plants (STP), 24.33 mg/L		
sediment (freshwater), 12.9 μg/kg sediment dw		
sediment (seawater), 1.29 µg/kg sediment dw		
soil, 1.17 μg/kg soil dw		

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025



Version 4.0. Supersedes version: 3.0 Page 5 / 12

8.2 Exposure controls

Additional advice on system design Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance

requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Respiratory protection not applicable

Thermal hazards No information available.

Delimitation and monitoring of the environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state liquid **Form** liquid Color yellowish Odor characteristic

Odour threshold No information available.

pH-value not applicable not applicable pH-value [1%] Boiling point or initial boiling point not applicable

and boiling range [°C]

Flash point [°C] 241

Flammability Not explosive. not self-igniting Lower explosion limit Upper explosion limit not applicable

Oxidising properties

Vapour pressure/gas pressure [kPa] No information available. Density [g/cm³] 0,85 (20 °C / 68,0 °F) Relative density not determined Bulk density [kg/m³] not applicable Solubility in water immiscible

Solubility other solvents No information available. Partition coefficient n-octanol/water No information available.

(log value)

Kinematic viscosity 56 mm²/s 40°C (DIN 51562) Relative vapour density No information available. Melting point [°C] No information available.

Auto-ignition temperature [°C] not applicable

Decomposition temperature [°C] No information available.

Particle characteristics not applicable

Other information

No information available.

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025

Version 4.0. Supersedes version: 3.0

Page 6 / 12

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents. Reactions with strong alkalies. Reactions with strong acids.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Strong oxidizing agent. See SECTION 10.3.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

ebi

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025

Version 4.0. Supersedes version: 3.0

Page 7 / 12

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute oral toxicity

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

LD50, oral, Rat, > 2000 mg/kg bw, OECD 423

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, oral, Rat, 5000 mg/kg bw

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

LD50, oral, Rat, 2000 mg/kg bw (OECD 401)

NOAEL, oral, 150 mg/kg bw/day

Acute dermal toxicity

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

LD50, dermal, Rat, > 2000 mg/kg bw, OECD 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw

Acute inhalational toxicity

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h

Serious eye damage/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

Eye, Rabbit, OECD 405, Causes serious eye damage.

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

Eye, non-irritating

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

dermal, Rabbit, OECD 404, no adverse effect observed

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-irritating

Respiratory or skin sensitisation

Based on the available information, the classification criteria are not fulfilled.

May produce an allergic reaction.

Calculation method

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

dermal, Guinea pig, OECD 406, sensitising

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-sensitizing

Specific target organ toxicity — single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025



Version 4.0. Supersedes version: 3.0

Page 8 / 12

NOAEL, oral, Rat, 125 mg/kg bw/day, OECD 408, adverse effect observed

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, inhalative, Rat, 980 mg/m³ air, no adverse effect observed

LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.

LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

in vitro, OECD 473, positive

mouse, OECD 474, negativ

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

in vitro, negativ

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

- Development

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

NOAEL, oral, Rat, 400 mg/kg bw/day, OECD 414, no adverse effect observed

CarcinogenicityBased on the available information, the classification criteria are not fulfilled.Aspiration hazardBased on the available information, the classification criteria are not fulfilled.

General remarks

The toxiclogical data are those of the pure product.

11.2 Information on other hazards

11.2.1 Endocrine disrupting

properties

Does not contain a relevant substance that meets the classification criteria.

11.2.2 Other information none

SECTION 12: Ecological information

12.1 Toxicity

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

LC50, (96h), Fish, 38 mg/l, OECD 203

EC50, (48h), Daphnia magna, 53 mg/l, OECD 202

EC50, (72h), Algae, 79 mg/l, OECD 201

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOELR, (14d), Fish, 1 g/L

LL50, (96h), Invertebrates, 10 g/L

LL50, (96h), Fish, 100 mg/L

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

EC50, (96h), Algae, 6.4 - 15 mg/L

EC50, (3h), Microorganisms, 2.433 g/L

EL50, (48h), Invertebrates, 91.4 mg/L

EL50, (21d), Invertebrates, 660 - 910 μ g/L

LL50, (96h), Fish, 24 mg/L

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025

Version 4.0. Supersedes version: 3.0

Page 9 / 12

12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant not determined Biological degradability not determined

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

< 10%, OECD 301 B, The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

BCF, < 10, OECD 305

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Does not contain a relevant substance that meets the classification criteria.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended) 130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025

Version 4.0. Supersedes version: 3.0

Page 10 / 12

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to

not applicable

ADR/RID

Inland navigation (ADN) not applicable

Marine transport in accordance with not applicable

IMDG

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

NO DANGEROUS GOODS

ADR/RID

Inland navigation (ADN) NO DANGEROUS GOODS

IMDG

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

no

ADR/RID

Inland navigation (ADN) no

Marine transport in accordance with no

IMDG

Air transport in accordance with IATA no

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025



Version 4.0. Supersedes version: 3.0 Page 11 / 12

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EG (2000/532/EC); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707

- Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

- Annex XIV (REACH) According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain

any substances ≥ 0.1% that are subject to authorisation.

- Annex XVII (REACH) According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains ≥ 0.1%

of substances with the following restrictions. 75

According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to

any restrictions.

TRANSPORT-REGULATIONS ADR (2025); IMDG-Code (2025, 42. Amdt.); IATA-DGR (2025)

NATIONAL REGULATIONS (UK): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe

employment restrictions for young people.

- VOC (2010/75/CE) not relevant

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H304 May be fatal if swallowed and enters airways.

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.01.2025, Revision 21.01.2025



Version 4.0. Supersedes version: 3.0 Page 12 / 12

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position

 $3.2,\, 9.1,\, 11.1,\, 11.2,\, 12.1,\, 12.6,\, 15.1,\, 16.3$