Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 1 / 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Engine Oil 5W - 40

Article number: 32936, 32937, 32938, 32939, 32940, 72936, 72938,

72939, 77940

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1 Relevant uses

Engine oil

### 1.2.2 Uses advised against

None known.

### 1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

### 1.4 Emergency telephone number

**Advisory body** +49 (0)89-19240 (24h) (English)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms none
Signal word none
Hazard statements none
Precautionary statements none

**Special labelling** EUH210 Safety data sheet available on request.

2.3 Other hazards

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

If swallowed or in the event of vomiting, risk of product entering the lungs.

**Environmental hazards**Does not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards Further hazards were not determined with the current level of knowledge.

## **SECTION 3: Composition / Information on ingredients**

### 3.1 Substances

not applicable

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 2 / 11

#### 3.2 Mixtures

### The product is a mixture.

Range [%]	Substance
25 - 50	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304

Comment on component parts

For full text of H-statements: see SECTION 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

**General information** Take off contaminated clothing and wash before reuse.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

**Ingestion** Consult a doctor immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

## 4.2 Most important symptoms and effects, both acute and delayed

No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to your doctor.

## **SECTION 5: Fire-fighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media Fire extinguishing method of surrounding areas must be considered.

Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

e used

Full water jet

## 5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Phosphorus oxides (POx). Sulphur oxides (SOx). Nitrogen oxides (NOx).

## 5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 3 / 11

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

Ensure adequate ventilation.

### 6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

## 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

### 6.4 Reference to other sections

See SECTION 8+13

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Avoid formation of aerosols.

Do not smoke.

Fire class (DIN EN 2): B

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container. Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container tightly closed. Protect from heat/overheating.

## 7.3 Specific end use(s)

See product use, SECTION 1.2

Date printed 27.09.2024, Revision 27.09.2024



Page 4 / 11 Version 1.0

## **SECTION 8: Exposure controls / personal protection**

#### **Control parameters** 8.1

Ingredients with occupational exposure limits to be monitored (UK)

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)

CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX

Long-term exposure: 5 mg/m³, oil mist

Short-term exposure (15-minute): 10 mg/m<sup>3</sup>

### Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

**DNEL** 

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m<sup>3</sup>

Industrial, inhalative, Long-term - local effects, 5.58 mg/m<sup>3</sup>

Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day

general population, inhalative, Long-term - local effects, 1.19 mg/m3

general population, oral, Long-term - systemic effects, 740 µg/kg bw/day

**PNEC** 

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

oral (food), 9,33 mg/kg

#### 8.2 Exposure controls

Additional advice on system design Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance

requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General exposure limit for oil mist should be noted.

Eye protection If there is a risk of splashing:

safety glasses

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

>0,11 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).

Skin protection light protective clothing

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear

appropriate respiratory protection.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 5 / 11

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical stateliquidFormliquidColorbrown

Odor like mineral oil
Odour threshold not relevant
pH-value not applicable
pH-value [1%] not applicable

Boiling point or initial boiling point

and boiling range [°C]

No information available.

Flash point [°C] 220 (ISO 2592)

Flammability No information available.

Lower explosion limit0,6 Vol.-%Upper explosion limit6,5 Vol.-%Oxidising propertiesno

Vapour pressure/gas pressure [kPa] No information available.

**Density [g/cm³]** 0,859 (DIN 51757) (15 °C / 59,0 °F)

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water immiscible

Solubility other solvents No information available.

Partition coefficient n-octanol/water No information available.

(log value)

Kinematic viscosity 82,8 mm<sup>2</sup>/s (40°C) (DIN 51562/T1)

Relative vapour density

Melting point [°C]

Auto-ignition temperature [°C]

Decomposition temperature [°C]

Particle characteristics

No information available.

No information available.

No information available.

9.2 Other information

Pour point: -39

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No dangerous reactions known if used as directed.

## 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

### 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

### 10.4 Conditions to avoid

Strong heating.

# Safety Data Sheet (UK REACH) (UK) Engine Oil 5W - 40

## Ferdinand Bilstein GmbH + Co. KG

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 6 / 11

## 10.5 Incompatible materials

Oxidizing agent

## 10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occure: Hydrogen sulfide (H2S).

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 7 / 11

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, oral, Rat, 5000 mg/kg bw

### Acute dermal toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

### Acute inhalational toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

**Skin corrosion/irritation**Based on the available information, the classification criteria are not fulfilled.

Respiratory or skin sensitisation Based on the available information, the classification criteria are not fulfilled.

**Specific target organ toxicity** — Based on the available information, the classification criteria are not fulfilled.

single exposure

**Specific target organ toxicity** — Based on the available information, the classification criteria are not fulfilled. **repeated exposure** 

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEC, inhalative, Rat, 980 mg/m³ air

LOAEL, oral, Rat, 125 mg/kg bw/day

MutagenicityBased on the available information, the classification criteria are not fulfilled.Reproduction toxicityBased on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

- Development

No information available.

## Safety Data Sheet (UK REACH) (UK) Engine Oil 5W - 40

### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 8 / 11

CarcinogenicityBased on the available information, the classification criteria are not fulfilled.Aspiration hazardBased on the available information, the classification criteria are not fulfilled.

**General remarks** 

Toxicological data of complete product are not available.

11.2 Information on other hazards

11.2.1 Endocrine disrupting

properties

Contains no ingredients with endocrine-disrupting properties.

11.2.2 Other information none

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

EL50, (48h), Invertebrates, 10 g/L

NOELR, (14d), Fish, 1 mg/L

LL50, (96h), Invertebrates, 10 g/L

LL50, (96h), Fish, 100 mg/L

## 12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant

Can be separated out mechanically in purification plants.

**Biological degradability** 

The product is only slightly biodegradable.

Slightly eliminable from water.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

The product is not readily biodegradable.

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

## 12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

### 12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment.

Date printed 27.09.2024, Revision 27.09.2024



Page 9 / 11 Version 1.0

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

**Product** 

In according to RoHS!

Coordinate disposal with the disposal contractor/authorities if necessary.

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended) 130205\* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110\* packaging containing residues of or contaminated by hazardous substances

### **SECTION 14: Transport information**

### 14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

**IMDG** 

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

**IMDG** 

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to

not applicable

ADR/RID

Inland navigation (ADN) not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

# Safety Data Sheet (UK REACH) (UK) Engine Oil 5W - 40

### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 10 / 11

### 14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with

**IMDG** 

not applicable

Air transport in accordance with IATA not applicable

### 14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with

**IMDG** 

Air transport in accordance with IATA no

### 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

## 14.7 Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**EEC-REGULATIONS** 2008/98/EG (2000/532/EC ); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707

- Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

- Annex XIV (REACH) According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain

any substances  $\geq$  0.1% that are subject to authorisation.

- Annex XVII (REACH) According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product does not

contain any substances ≥ 0.1% that are restricted.

According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to

arry restrictions

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

NATIONAL REGULATIONS (UK): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

- Observe employment restrictions

for people

Observe employment restrictions for young people.

- VOC (2010/75/CE) 0 %

### 15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

## Safety Data Sheet (UK REACH) (UK) Engine Oil 5W - 40

### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.09.2024, Revision 27.09.2024



Version 1.0 Page 11 / 11

### **SECTION 16: Other information**

## 16.1 Hazard statements (SECTION 3)

H304 May be fatal if swallowed and enters airways.

### 16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

### 16.3 Other information

Classification procedure

Modified position none