

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Gear oil
Article number: 39070, 39071, 109672, 194480

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms none

Signal word none

Hazard statements none

Precautionary statements none

Special labelling EUH210 Safety data sheet available on request.

Contains: 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate. EUH208 May produce an allergic reaction.

2.3 Other hazards

Human health dangers If swallowed or in the event of vomiting, risk of product entering the lungs.
Frequent persistent contact with the skin can cause skin irritation.
The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Environmental hazards Does not contain any PBT or vPvB substances.
The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.02.2025, Revision 05.02.2025

Version 13.0. Supersedes version: 12.0

Page 2 / 14

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
20 - < 50	Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
20 - < 50	Distillates (petroleum), hydrotreated light paraffinic
	CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 5	Isooctadecanoic acid, reaction products with tetraethylenepentamine
	CAS: -, EINECS/ELINCS: 701-204-9, Reg-No.: 01-2119960832-33-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Eye Irrit. 2: H319
0,1 - < 0,25	4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate
	CAS: 93882-40-7, EINECS/ELINCS: 299-434-3, Reg-No.: 01-2120735527-50-XXXX
	GHS/CLP: Skin Sens. 1: H317 - Eye Irrit. 2: H319 - Aquatic Chronic 2: H411

Comment on component parts

For full text of H-statements: see SECTION 16.
Contains less than 3% w/w DMSO-extract (only for mineral oils)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Seek medical advice immediately. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
If swallowed or in the event of vomiting, risk of product entering the lungs.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Foam, dry powder, water spray jet, carbon dioxide.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Use only in well-ventilated areas.
The product is combustible.
Do not eat, drink or smoke when using this product.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Cloths contaminated with product should not be kept in trouser pockets.
Contaminated work clothing should not be allowed out of the workplace.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with food and animal food/diet.
Keep container in a well-ventilated place.
Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
Long-term exposure: 5 mg/m ³ , oil mist
Short-term exposure (15-minute): 10 mg/m ³
Distillates (petroleum), hydrotreated light paraffinic
CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX
Long-term exposure: 5 mg/m ³ , ACGIH TLV (OIL MIST)

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1.19 mg/m ³
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0,97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,74 mg/kg bw/day
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
Industrial, inhalative, Long-term - systemic effects, 3.526 mg/m ³ (AF= 75)
Industrial, dermal, Long-term - systemic effects, 2 mg/kg bw/d (AF= 300)
general population, oral, Long-term - systemic effects, 0.5mg/kg bw/day
Isooctadecanoic acid, reaction products with tetraethylenepentamine, CAS: -
worker, inhalative, Long-term - systemic effects, 11.75 mg/m ³
worker, dermal, Long-term - systemic effects, 3.33 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 2.9 mg/m ³
general population, dermal, Long-term - systemic effects, 1.67 mg/kg bw/day
general population, oral, Long-term - systemic effects, 1.67 mg/kg bw/day

PNEC

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (food), 9,33 mg/kg
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
oral (food), 9,33 mg/kg food
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
freshwater, 0.009 mg/L (AF= 1000)
seawater, 0.001 mg/L (AF= 10 000)
sewage treatment plants (STP), 100 mg/L (AF= 10)
sediment (freshwater), 542 229.75 mg/kg dw
sediment (seawater), 54 222.98 mg/kg dw
soil, 259 870.48 mg/kg dw
oral (food), 20 mg/kg food (AF=300)
Isooctadecanoic acid, reaction products with tetraethylenepentamine, CAS: -

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.02.2025, Revision 05.02.2025

Version 13.0. Supersedes version: 12.0

Page 5 / 14

freshwater, 460 µg/L
seawater, 46 µg/L
sediment (freshwater), 38100 mg/kg sediment dw
sewage treatment plants (STP), 1 g/l
sediment (seawater), 3810 mg/kg sediment dw
soil, 10 mg/kg soil dw
oral (food), 33.3 mg/kg food

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. General exposure limit for oil mist should be noted. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4mm: Nitrile rubber, >120 min (EN 374-1/-2/-3). > 0,4mm: butyl rubber, > 120 min (EN 374)
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Respiratory protection	Breathing apparatus in the event of aerosol or mist formation. Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	light yellow
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	215 °C / 419 °F
Flammability	Not explosive.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/cm³]	0,84 (DIN 51757) (15 °C / 59,0 °F)
Relative density	No information available.
Bulk density [kg/m³]	not applicable
Solubility in water	virtually insoluble
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	not applicable
Kinematic viscosity	33,2 mm²/s, 40 °C / 104 °F (DIN 51562)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	not applicable
Decomposition temperature [°C]	No information available.
Particle characteristics	not applicable

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known.

10.4 Conditions to avoid

No special measures necessary.

10.5 Incompatible materials

Oxidizing agent
Strong basic compounds
Strong acids.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product
ATE-mix, oral, > 5000 mg/kg bw
Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, oral, Rat, > 5000 mg/kg bw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, oral, Rat, 5000 mg/kg bw
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
LD50, oral, Rat, > 10 000 mg/kg bw
Isooctadecanoic acid, reaction products with tetraethylenepentamine, CAS: -
LD50, oral, Rat, 5000 mg/kg bw

Acute dermal toxicity

Product
dermal, Based on the available information, the classification criteria are not fulfilled.
Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, dermal, Rabbit, > 5000 mg/kg bw
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
LD50, dermal, Rat, > 3160 mg/kg
Isooctadecanoic acid, reaction products with tetraethylenepentamine, CAS: -
LD50, dermal, Rabbit, 2000 mg/kg bw

Acute inhalational toxicity

Product
inhalative, Based on the available information, the classification criteria are not fulfilled.
Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air, 4h
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h

Serious eye damage/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
Eye, non-irritating
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
Eye, irritant

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
dermal, non-irritating

Respiratory or skin sensitisation

Based on the available information, the classification criteria are not fulfilled.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.02.2025, Revision 05.02.2025

Version 13.0. Supersedes version: 12.0

Page 9 / 14

EUH208: May produce an allergic reaction.
Calculation method

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
dermal, non-sensitizing
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
dermal, sensitising

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
inhalative, no adverse effect observed

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEL, dermal, Rabbit, 1000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m ³ air
LOAEL, oral, Rat, 125 mg/kg bw/day
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
NOAEC, inhalative, Rat, 980 mg/m ³ (subacute), no adverse effect observed
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.
LOAEL, dermal, mouse, 100 mg/kg bw/day (chronic), The effects observed are not sufficient for classification.
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
NOAEL, oral, Rat, 300 mg/kg bw/day
Isooctadecanoic acid, reaction products with tetraethylenepentamine, CAS: -
NOAEL, oral, Rat, 1000 mg/kg bw/day

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
in vitro, negativ
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
in vitro, negativ

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
NOAEL, oral, Rat, 450 mg/kg bw/day

- Development

Substance
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
NOAEL, oral, Rat, 450 mg/kg bw/day

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.02.2025, Revision 05.02.2025

Version 13.0. Supersedes version: 12.0

Page 10 / 14

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.
On basis of test data

General remarks Toxicological data of complete product are not available.
The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

11.2.2 Other information none

SECTION 12: Ecological information

Product

12.1 Toxicity

Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

EC50, (48h), > 10000 mg/l (Gammarus pulex), OECD 202

EC50, (72h), Algae, > 100 mg/l

NOEC, (72h), Pseudokirchneriella subcapitata, ≥ 100 mg/l, OECD 201

NOEC, (21d), Daphnia magna, 10 mg/l, OECD 211

LL50, (96h), Fish, > 100 mg/l, OECD 203

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

NOELR, (14d), Fish, 1 g/L

LL50, (96h), Invertebrates, 10 g/L

LL50, (96h), Fish, 100 mg/L

4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7

LC50, (96h), Fish, > 100 mg/l (OECD 203)

EL50, (48h), Daphnia magna, 9,5 mg/l (OECD 202)

NOEC, (72h), Algae, > 100 mg/l (OECD 201)

Isooctadecanoic acid, reaction products with tetraethylenepentamine, CAS: -

LC50, (96h), Fish, 1 g/L

EC50, (48h), Invertebrates, 1 g/L

EC50, (96h), Algae, 44 - 94 mg/L

NOEC, (21d), Invertebrates, 32 mg/L

12.2 Persistence and degradability

Behaviour in environment compartments No information available.

Behaviour in sewage plant No information available.

Biological degradability

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

(28d), 31 %, OECD 301 F, The product is not readily biodegradable.

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

(28d), 31 %, OECD 301 F, The product is not readily biodegradable.



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.02.2025, Revision 05.02.2025

Version 13.0. Supersedes version: 12.0 Page 11 / 14

12.3 Bioaccumulative potential

Substance
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
log Pow, > 3,5

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Ecological data of complete product are not available.
Do not discharge product unmonitored into the environment or into the drainage.
The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Disposal in an incineration plant in accordance with the regulations of the local authorities.
In according to RoHS!

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances
150102
150104

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.02.2025, Revision 05.02.2025

Version 13.0. Supersedes version: 12.0 Page 12 / 14

14.2 UN proper shipping name

Transport by land according to ADR/RID	NO DANGEROUS GOODS
Inland navigation (ADN)	NO DANGEROUS GOODS
Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID	no
Inland navigation (ADN)	no
Marine transport in accordance with IMDG	no
Air transport in accordance with IATA	no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.02.2025, Revision 05.02.2025

Version 13.0. Supersedes version: 12.0 Page 13 / 14

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
EEC-REGULATIONS	2008/98/EG (2000/532/EC); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances ≥ 0.1% that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains ≥ 0.1% of substances with the following restrictions. 75 According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to any restrictions.
TRANSPORT-REGULATIONS	ADR (2025); IMDG-Code (2025, 42. Amdt.); IATA-DGR (2025)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	no
- VOC (2010/75/CE)	0 %
15.2 Chemical safety assessment	not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)	H411 Toxic to aquatic life with long lasting effects. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H315 Causes skin irritation. H304 May be fatal if swallowed and enters airways.
---	---

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position 2.3, 3.2